

FLOOR TILE



Beige



Grey




Anthracite



Brown

FASCIA 12 x 24



Beige



Grey



Anthracite



Brown

DECORATIVE MODULO 12 x 12



Anthracite



Brown

USAGE

Floors	Walls	Countertops
F	W	C



ANTHRACITE - GREY

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	(23-7/16" x 47-1/16") (59.50 cm x 119.50 cm)	7/16"	15.5	2
	12 x 48 Floor Tile	(11-11/16" x 47-1/16") (29.65 cm x 119.50 cm)	7/16"	11.63	3
	24 x 24 Floor Tile	(23-7/16" x 23-7/16") (59.50 cm x 59.50 cm)	7/16"	11.63	3
	12 x 24 Floor Tile	(11-11/16" x 23-7/16") (29.65 cm x 59.50 cm)	7/16"	9.69	5
	Fascia Deco 12 x 24	(11-11/16" x 23-7/16") (29.65 cm x 59.50 cm)	High - low 7/16" - 5/8"	7.75	4
	Modulo Deco 12 x 12	(11-13/16" x 11-13/16" Sheet) (30.00 cm x 30.00 cm)	High - low 7/16" - 5/8"	3.88	4

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■*
Wet & Level - Interior Floor	≥ 0.42	■*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest®, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

*Floor tile only

TRIM

Description	Size	Shape
Floor Bullnose	4 x 24	
Cove Base	6 x 12	
Cove Base Outcorner	1 x 6	
Cove Base Incorner	1 x 6	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a Floor pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Deco Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

	Floor Tile				Decos		Trim			
	24 x 48	12 x 48	24 x 24	12 x 24	12 x 24 Fascia Deco	12 x 12 Modulo Deco	4 x 24 Floor Bullnose	6 x 12 Cove Base	1 x 6 Cove Base Outcorner	1 x 6 Cove Base Incorner
Anthracite	M6XW	M6YN	M6X0	M6X4	M70C	M6Z9	M70U	UHCR	UHCZ	UHCV
Beige			M6XX	M6X1	M70E		M70Q	UHCN	UHCW	UHCS
Brown			M6XZ	M6X3	M70D	M70A	M70T	UHCQ	UHCY	UHCU
Grey	M6XU	M6YL	M6XY	M6X2	M70F		M70R	UHCP	UHCX	UHCT



Floor Tile



Wall Tile



TruEdge™



Reveal Imaging®



Pre-Consumer
Recycled Content



CERTIFIED
PORCELAIN
TILE

All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

FLOOR TILE