ESALE STONE

GLAZED PORCELAIN

REVEAL IMAGING®

FLOOR TILE







Sand

1 x 1 SQUARE MOSAIC 13 x 13 SHEET



Rust



Smoke





Moss



Moss

2 x 2 SQUARE MOSAIC 13 x 13 SHEET



Sand







Smoke



Moss

$2 \times 3^{-1}/_{2}$ DIAMOND MOSAIC 13 x 13 SHEET



Rust



Moss



Smoke

Sand USAGE

Floors	Walls	Countertops
F	W	С



SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
20 x 20 Floor Tile	(19-11/16" x 19-11/16") (50.00 cm x 50.00 cm)	3/8"	18.83	7
10 x 20 Floor Tile	(9-3/4" x 19-11/16") (24.80 cm x 50.00 cm)	3/8"	13.46	10
13 x 13 Floor Tile	(13-1/8" x 13-1/8") (33.30 cm x 33.30 cm)	5/16"	17.9	15
6-1/ ₂ x 6-1/ ₂ Floor Tile	(6-1/2" x 6-1/2") (16.50 cm x 16.50 cm)	5/16"	10.55	36
2 x 3-1/2 Diamond (Mesh-mounted)	(13" x 13" Sheet) (33.02 cm x 33.02 cm)	5/16"		10
2 x 2 Square Mosaic (Mesh-mounted)	(13" x 13" Sheet) (33.02 cm x 33.02 cm)	5/16"		10
1 x 1 Square Mosaic (Mesh-mounted)	, ,			10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	•
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	•
Pool Linings	N/A	*

A DCOF value of \ge 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest $^{"}$, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left($

*Mosaic tile only.

TRIM

Description	Size	Shape	
Floor Bullnose	3 x 13		

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)	Random Variation
Mosaic: 1/8"	

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.Use of a latex modified thin-set is recommended for installation. For more information, visit marazzitile.com.

Use of a latex modified thin-set is recommended for installation. For more information, marazzitile.com.

	Floor Tile			Deco			Trim	
	20 x 20	10 x 20	13 x 13	6-1/2 x 6-1/2	1 x 1 Square Mosaic 13 x 13 Sheet	2 x 2 Square Mosaic 13 x 13 Sheet	2 x 3-1/ ₂ Diamond Mosaic 13 x 13 Sheet	3 x 13 Floor Bullnose
Moss	UF2Q	UF2G	UF2L	UF2A	UF2Y	UF24	UF28	UF2U
Rust	UF2R	UF2H	UF2M	UF2B	UF2Z	UF25	UF29	UF2V
Sand	UF2S	UF2J	UF2N	UF2C	UF22	UF26	UF3A	UF2W
Smoke	UF2T	UF2K	UF2P	UF2D	UF23	UF27	UF3B	UF2X







Reveal Imaging®



Pre-Consumer Recycled Content



