

# **FLOOR TILE**





Elegant Sophisticated

Distinguished

# 2 x 2 SQUARE MOSAIC 12 x 12 SHEET









# **MIXED DECOS**



Tilxed Floodie IE X IE offeet



Listelli 2 x 12

## USAGE

Floors	Walls	Countertops
F	W	С



#### **SIZES**

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
18 x 36 Floor Tile	(17-11/16" x 35-7/16") (45.00 cm x 90.00 cm)	3/8"	13.44	3
20 x 20 Floor Tile	(19-11/16" x 19-11/16") (50.00 cm x 50.00 cm)	3/8"	16.15	6
12 x 24 Floor Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	3/8"	17.37	9
2 x 2 Square Mosaic (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm)	5/16"		10
Mixed Mosaic (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm)	5/16"		10
 Listelli 2 x 12	(2" x 12") (30.48 cm x 30.48 cm)	3/8"		6

## **APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	*

A DCOF value of  $\geq$  0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest", visit marazzitile.com/DCOF.

## **APPLICATION NOTES:**

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

\*2 x 2 Mosaic tile only.

#### **TRIM**

Description	Size	Shape			
Floor Bullnose	4 × 24				
Cove Base	6 x 12				
Cove Base Outcorner	1 x 6				
Cove Base Incorner	1 x 6	Û			

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

### INSTALLATION

Grout Joint Recommendation	<b>Shade Variation</b>
<b>Floor:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	V3 High Variation
Mosaic: 1/8"	

# PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

## **NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazzitile.com.

	Floor Tile			Deco			Trim			
	20 x 20	18 x 36	12 x 24	2 x 2 Square Mosaic 12 x 12 Sheet	Mixed Mosaic 12 x 12 Sheet	2 x 12 Listelli	4 x 24 Floor Bullnose	6 x 12 Cove Base	1 x 6 Cove Base Outcorner	1 x 6 Cove Base Incorner
Distinguished	ULBS	ULBP	ULBL	ULEW			ULBV	ULC6	ULC3	ULBY
Elegant	ULBQ	ULBM	ULBJ	ULEU			ULBT	ULC4	ULBZ	ULBW
Sophisticated	ULBR	ULBN	ULBK	ULEV			ULBU	ULC5	ULC2	ULBX
Mixed					ULE8	ULEE				





Wall Tile



Reveal Imaging®



Pre-Consumer Recycled Content



