

Field Tile Sizes



Alabaster - A

TCRMFL36A - 12"x24" Matte
TCRMFL36AP - 12"x24" Polished
TCRMFL49A - 18"x36" Matte
TCRMFL60A - 24"x24" Matte
TCRMFL60AP - 24"x24" Polished



Silver - S

TCRMFL36S - 12"x24" Matte
TCRMFL36SP - 12"x24" Polished
TCRMFL49S - 18"x36" Matte
TCRMFL60S - 24"x24" Matte
TCRMFL60SP - 24"x24" Polished



Bianco - B

TCRMFL36B - 12"x24" Matte
TCRMFL36BP - 12"x24" Polished
TCRMFL49B - 18"x36" Matte
TCRMFL60B - 24"x24" Matte
TCRMFL60BP - 24"x24" Polished



Crema - C

TCRMFL36C - 12"x24" Matte
TCRMFL36CP - 12"x24" Polished
TCRMFL49C - 18"x36" Matte
TCRMFL60C - 24"x24" Matte
TCRMFL60CP - 24"x24" Polished



Noce - N

TCRMFL36N - 12"x24" Matte
TCRMFL36NP - 12"x24" Polished
TCRMFL49N - 18"x36" Matte
TCRMFL60N - 24"x24" Matte
TCRMFL60NP - 24"x24" Polished

2"x2" Mosaic - Matte (12"x12" Sheet)



Alabaster - A

TCRMFL221A



Silver - S

TCRMFL221S



Bianco - B

TCRMFL221B



Crema - C

TCRMFL221C



Noce - N

TCRMFL221N

2"x2" Hexagon Mosaic - Matte (12"x12" Sheet)



Alabaster - A

TCRMFL221HEXA



Silver - S

TCRMFL221HEXS



Bianco - B

TCRMFL221HEXB



Crema - C

TCRMFL221HEXC



Noce - N

TCRMFL221HEXN

2"x6" Chevron Mosaic - Polished (9 1/2"x11 3/4" Sheet)



Alabaster - A
TCRMFLCHVAP



Silver - S
TCRMFLCHVSP



Bianco - B
TCRMFLCHVBP



Crema - C
TCRMFLCHVCP




Noce - N
TCRMFLCHVNP

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRMFL36•	12"x24"	Field Tile - Matte	9	18.00
		Ø TCRMFL36•P	12"x24"	Field Tile - Polished	9	18.00
		TCRMFL49•	18"x36"	Field Tile - Matte	4	18.00
		TCRMFL60•	24"x24"	Field Tile - Matte	4	16.00
		Ø TCRMFL60•P	24"x24"	Field Tile - Polished	4	16.00
		Ø TCRMFLAC•	1"x1"	Beak - Matte	-	-
Trim		Ø TCRMFLA112•	1"x12"	Quarter Round - Matte	80	-
		TCRMFLS320•	3"x20"	Surface Bullnose - Matte	32	-
		Ø TCRMFLS324•P	3"x24"	Surface Bullnose - Polished	26	-
		Ø TCRMFLCHV•P	9 1/2"x11 3/4" Sheet	2"x6" Chevron Mosaic - Polished	14	-
Mosaic		TCRMFL221•	12"x12" Sheet	2"x2" Mosaic - Matte	12	-
		TCRMFL221HEX•	12"x12" Sheet	2"x2" Hexagon Mosaic - Matte	11	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 550 lbf	≤ 0.5%	Unaffected




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	
Light Commercial	•	◻	◻	•	◻	
Commercial	•	◻	◻	•	◻	



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- * Special Order only
- Ø Applications & ANSI Technical Specifications do not apply



Use of a leveling system during installation is strongly recommended

For installation of all polished, polished glazed, and honed porcelain tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners. Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make changes to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Reference the most current TCNA Handbook, ANSI, manufacturer's specifications, and the Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and/or use voids warranty. Please visit www.bedrosians.com for current product information.